



TITLE OF THE INVENTION

5                   TELEPHONE SET IDENTIFYING METHOD,  
                  TELEPHONE SET TYPE IDENTIFYING  
                  APPARATUS, PROCESSING APPARATUS AND  
                  STORAGE MEDIUM

BACKGROUND OF THE INVENTION

1. Technical Field of the Invention

10                   The present invention generally relates to  
                  telephone set identifying methods, telephone set  
                  type identifying apparatuses, processing apparatuses  
                  and storage mediums, and more particularly to a  
                  telephone set identifying method and a telephone set  
15                   type identifying apparatus for identifying a type of  
                  a portable telephone set such as a mobile telephone  
                  set and a personal handy-phone system (hereinafter  
                  simply referred to as PHS) telephone set which is  
                  coupled to a data processing apparatus such as a  
20                   personal computer and for notifying the identified  
                  type to the data processing apparatus, a processing  
                  apparatus, and to a computer-readable storage medium  
                  which stores a program for causing a computer which  
                  couples the data processing apparatus to the  
25                   portable telephone set to identify the type of the  
                  portable telephone set.

                  In this specification, portable telephones  
                  capable of making a communication while moving will  
                  be referred to as mobile telephone sets, as opposed  
                  to PHS telephone sets which are not suited for  
30                   making a communication while moving.

2. Description of the Related Art

                  Recently, the use of portable telephone  
                  sets such as mobile telephone sets and PHS telephone  
                  sets have become popular. With the popular use of  
35                   the portable telephone sets, it has also become  
                  popular to make a data communication using the  
                  portable telephone set. However, when viewed from a

data processing apparatus such as a personal computer (hereinafter also referred to as PC), a data circuit equipment (DCE) which can be controlled is designed for a connection system and a  
5 communication protocol which are completely different depending on the portable telephone set which is coupled to the DCE.

In other words, conventionally, the DCE is designed depending on the type of portable telephone  
10 set to which the personal computer is coupled. For this reason, when connecting the mobile telephone set, it is necessary to couple a DCE which is designed for the connection system and the  
15 communication protocol of the mobile telephone set. the personal computer and the mobile telephone set. On the other hand, when connecting the PHS telephone set, it is necessary to couple a DCE which is designed for the connection system and the  
20 communication protocol of the PHS telephone set between the personal computer and the PHS telephone set.

Conventionally, it is thus necessary to design and manufacture the DCE exclusively for each type of portable telephone set. For this reason,  
25 there was a problem in that the DCEs cannot be manufactured at a low cost.

In addition, there was another problem in that a troublesome operation is required by the user and that a load on the user is large, because of the  
30 need to connect the DCE which is designed exclusively for the type of portable telephone set which is to be coupled to the personal computer, every time a data communication or the like is carried out using the personal computer. More  
35 particularly, in a case where the DCE is mounted on a PC card or the like, it was necessary to insert and connect with respect to the personal computer a

104260-663560

5

10

15

20

25

30

35

A further object of the present invention

is to provide a telephone set identifying method for identifying a type of portable telephone set to which a data processing apparatus is coupled, comprising the steps of identifying the type of the portable telephone set based on a waveform of a signal output from a specific terminal of a data interface part of the portable telephone set. In this case, it is possible to positively identify the type of the portable telephone set immediately when the portable telephone set outputs a synchronizing signal.

Another object of the present invention is to provide a telephone set identifying method for identifying a type of portable telephone set to which a data processing apparatus is coupled, comprising the steps of identifying the type of the portable telephone set based on an allocation pattern of input and output terminals of a data interface part of the portable telephone set. In this case, it is possible to positively identify the type of the portable telephone set immediately when the portable telephone set is coupled.

Still another object of the present invention is to provide a telephone set type identifying apparatus for identifying a type of portable telephone set to which a data processing apparatus is coupled, comprising means for identifying the type of the portable telephone set based on a response with respect to an operation start signal which is output to a data interface part of the portable telephone set. In this case, it is possible to positively identify the type of the portable telephone set being coupled.

A further object of the present invention is to provide a telephone set type identifying apparatus for identifying a type of portable telephone set to which a data processing apparatus

5

10

20

25

35

couples to a portable telephone set to identify a type of the portable telephone set, comprising means for causing the computer to identify the type of the portable telephone set based on a pattern of an  
5 asynchronous signal output from a data interface part of the portable telephone set. In this case, it is possible to positively identify the type of the portable telephone set immediately when the portable telephone set outputs a control signal.

10 Another object of the present invention is to provide a computer-readable storage medium which stores a program for causing a computer which couples to a portable telephone set to identify a type of the portable telephone set, comprising means  
15 for causing the computer to identify the type of the portable telephone set based on an allocation pattern of input and output terminals of a data interface part of the portable telephone set. In this case, it is possible to positively identify he  
20 type of the portable telephone set immediately when the portable telephone set is coupled.

Therefore, according to the present invention, it is possible to automatically identify the type of portable telephone set which is coupled  
25 to the data processing apparatus, so that the user does not need to be aware of the type of portable telephone set being coupled, and to realize an inexpensive DCE by making it possible to use a DCE having the same construction regardless of the type  
30 of the portable telephone set and to eliminate the need for a troublesome operation by the user so as to greatly reduce the load on the user.

Still another object of the present invention is to provide a processing apparatus  
35 operatively coupled between a communication equipment and an information processing apparatus, comprising an identifying part identifying a type of

0005599-09410  
101550-555500

5

10

10

15

20

25

30

35

FIG. 9 is a diagram schematically showing





As shown in FIG. 2, the personal computer 1 generally includes a main body part 101 which includes a central processing unit (CPU), a disk drive unit and the like, a display 102 having a display screen 102a which displays an image in response to an instruction from the main body part

5

10

20

25

30

35

5

10

25

30

35

that is, a known mobile telephone set and a known PHS telephone set may be used as the portable telephone set 3, and the construction of the portable telephone set 3 is of course not limited to the construction shown in FIG. 4.

FIG. 5 is a diagram showing an allocation pattern of the input and output terminals of the connector 31 for the case where the portable telephone set 3 is a mobile telephone set. On the other hand, FIG. 6 is a diagram showing an allocation pattern of the input and output terminals of the connector 31 for the case where the portable telephone set 3 is a PHS telephone set. In FIGS. 5 and 6, the pin number of the input and output terminals is indicated on the left side, and the signal attribute corresponding to each pin number is indicated on the right side. In FIGS. 5 and 6, GND indicates the ground, OPEN indicates an open-circuit, TCH indicates an information transmission channel for transferring communication data (real data), ADP indicates an adapter, that is, the DCE 2, and CRC indicates a cyclic redundancy check.

The construction of the connector 31 is of course not limited to the construction shown in FIGS. 5 and 6. In addition, the connector 31 is not limited to the 16-pin connector, and the connector 31 may have an arbitrary number of pins.

FIG. 7 is a diagram showing an important part of the connection part 26 of this embodiment. In FIG. 7, the numbers assigned to the pins of the connector 29 are the same as the pin numbers assigned to the connector 31 shown in FIGS. 5 and 6. The connection part 26 includes a switch 261 which is connected to ports "a" through "i" of the CPU 22 and connects to the pin numbers "1" through "16" of the connector 29. In this embodiment, the switch 261 is switched by the CPU 22 so that the port "a"

connects to the pin number "1" or "2", the port "b" connects to the pin number "4", the port "c" connects to the pin number "5", the port "d" connects to the pin number "6", the port "e" connects to the pin number "7", the port "f" connects to the pin number "10", the port g connects to the pin number "3", the port "h" connects to the pin number "11", and the port "i" connects to the pin number "15". If the portable telephone set 3 being coupled is the PHS telephone set, the port "a" is connected to the pin number "1". On the other hand, the port "a" is connected to the pin number "2" if the portable telephone set 3 being coupled is the mobile telephone set. For example, the switching of the switch 261 may be set by the CPU 22 depending on the type of the portable telephone set 3 used or, may be set fixedly. In FIG. 7, the pin allocation is shown on the right side in correspondence with each of the pin numbers "1" through "16" of the connector 29 for both cases where the portable telephone set 3 is the mobile telephone set and the portable telephone set 3 is the PHS telephone set.

FIG. 8 is a flow chart for explaining the operation of the CPU 22 of the DCE 2 of this embodiment. When an operation start signal from the portable telephone set 3 is input to the port "h" or the port "i" of the CPU 22 to generate an interrupt, the process shown in FIG. 8 is called. In FIG. 8, a step S1 decides whether the operation start signal output from the portable telephone set 3 which is coupled to the DCE 2 is received at the port "h" or the port "i" of the CPU 22 via the connector 31, the cable 5, the connector 29 and the connection part 26. If an ADP power supply control signal is received by the port "i" as the operation start signal, a step Sa sets information which indicates the type of the

FIG. 9 is a diagram schematically showing the switching of control programs in this embodiment. In FIG. 9, a control (detection) program P1 of the CPU 22 identifies whether the coupled portable telephone set 3 is a mobile telephone set or a PHS telephone set, by carrying out the processes of the steps S1 through S3 shown in FIG. 8. In the case where the portable telephone set 3 is the mobile telephone set as a result of this identification, the control program of the CPU 22 is switched to a control program P11 for the mobile telephone set, and processes including the process of the step S4 shown in FIG. 8 are carried out. On the other hand, in the case where the portable telephone set 3 is the PHS telephone set as a result of this identification, the control program of the CPU 22 is switched to a control program P12 for the PHS telephone set, and processes including the process of the step S4 shown in FIG. 8 are carried out.

The switching of the control program can be made by reading the control program P11 or P12 from a program storage region of the ROM 23. In addition, in a case where it is necessary to switch the hardware connection between the switch 261 and the connector 29 within the connection part 26 of the DCE 2 (that is, switch the hardware connection

Next, a description will be given of a second embodiment of the telephone set identifying method according to the present invention. This second embodiment of the telephone set identifying method uses a second embodiment of the telephone set type identifying apparatus according to the present invention. The construction of the system applied with this second embodiment of the telephone set identifying method is the same as that applied with the first embodiment of the telephone set identifying method described above in conjunction with FIG. 1, and the basic construction of each part of the system in this second embodiment is the same as the basic construction of the corresponding part used in the first embodiment.

FIG. 10 is a flow chart for explaining the operation of the CPU 22 of the DCE 2 in this second embodiment. In FIG. 10, a step S11 transmits, as an operation start signal, a PHS telephone set control signal which is included in an up-control signal,



from the port "d" shown in FIG. 7 via the switch 261 of the connection part 26. As a result, the PHS telephone control signal which is output from the connection part 26 of the DCE 2 via the pin number "6" of the connector 29 is transmitted to the portable telephone set 3 via the cable 5 and the pin number "6" of the connector 31. A step S12 decides whether or not a response is received from the portable telephone set 3 which is a PHS telephone set. For example, the step S12 decides whether or not a response is received from the portable telephone set 3 which is a PHS telephone set, by deciding whether or not a down-control signal from the pin number "7" of the connector 31 of the portable telephone set 3 is received by the port "e" via the cable 5, the pin number "7" of the connector 29 and the switch 261 of the connection part 26.

If no response is received in the step S12, a step S13 waits for a predetermined time. Thereafter, a step S14 transmits, as an operation start signal, a mobile telephone control signal which is included in an up-control signal, from the port "d" via the switch 261 of the connection part 26. Hence, the mobile telephone control signal which is output from the connection part 26 of the DCE 2 via the pin number "6" of the connector 29 is transmitted to the portable telephone set 3 via the cable 5 and the pin number "6" of the connector 31. A step S15 decides whether or not a response is received from the portable telephone set 3 which is a mobile telephone set. For example, the step S15 decides whether or not a response is received from the portable telephone set 3 which is a mobile telephone set, by deciding whether or not a down-control signal from the pin number "7" of the connector 31 of the portable telephone set 3 is received by the port "e" via the cable 5, the pin

On the other hand, if a response is  
5 received in the step S12, a step S16 sets  
information which indicates the type of the portable  
telephone set 3 as the PHS telephone set. After the  
step S16, a step S17 issues a telephone set type  
primitive, so as to notify the identified type of  
10 the portable telephone set 3 to the personal  
computer 1 via the I/O control part 25, the  
connector 21 and the cable 4, and the process ends.

Next, a description will be given of a third embodiment of the telephone set identifying method according to the present invention. This third embodiment of the telephone set identifying method uses a third embodiment of the telephone set type identifying apparatus according to the present invention. The construction of the system applied with this third embodiment of the telephone set identifying method is the same as that applied with the first embodiment of the telephone set identifying method described above in conjunction with FIG. 1, and the basic construction of each part of the system in this third embodiment is the same as the basic construction of the corresponding part used in the first embodiment.

FIG. 11 is a flow chart for explaining the

operation of the CPU 22 of the DCE 2 in this third embodiment. The CPU 22 has a function of receiving a synchronizing signal which is output from the portable telephone set 3 which is coupled to the DCE 2 at the port "e" of the CPU 22 via the connector 31, the cable 5, the connector 29 and the connection part 26, and counting the synchronizing signal received at the port "e". For example, this synchronizing signal is a TCH clock having a frequency of 42 kHz in the case where the portable telephone set 3 is a mobile telephone set, and is a data transmitting and receiving clock having a frequency of 32 kHz or 64 kHz in the case where the portable telephone set 3 is a PHS telephone set. As shown in FIG. 12, the CPU 22 counts the number of high levels or low levels of the synchronizing signal for a predetermined time from a timer start time to a timer stop time of the CPU 22, and the process shown in FIG. 11 is called when this counting operation of the CPU 22 ends.

A step S21 inputs a counted value of the synchronizing signal, and a step S22 decides from the input counted value whether the frequency of the counted synchronizing signal matches the frequency (42 kHz) of the mobile telephone set or matches the frequency (32 kHz or 64 kHz) of the PHS telephone set. If the frequency of the synchronizing signal is 42 kHz, a step S23 sets information which indicates the type of the portable telephone set 3 as the mobile telephone set. On the other hand, if the frequency of the synchronizing signal is 32 kHz or 64 kHz, a step S24 sets information which indicates the type of the portable telephone set 3 as the PHS telephone set. After the step S23 or S24, a step S25 issues a telephone set type primitive, so as to notify the identified type of the portable telephone set 3 to the personal computer 1 via the

I/O control part 25, the connector 21 and the cable 4, and the process ends.

Next, a description will be given of a fourth embodiment of the telephone set identifying method according to the present invention. This fourth embodiment of the telephone set identifying method uses a fourth embodiment of the telephone set type identifying apparatus according to the present invention. The construction of the system applied with this fourth embodiment of the telephone set identifying method is the same as that applied with the first embodiment of the telephone set identifying method described above in conjunction with FIG. 1, and the basic construction of each part of the system in this fourth embodiment is the same as the basic construction of the corresponding part used in the first embodiment.

FIG. 13 is a flow chart for explaining the operation of the CPU 22 of the DCE 2 in this fourth embodiment. A down-control signal which is output from the portable telephone set 3 which is coupled to the DCE 2 is received by the port "e" of the CPU 22 via the connector 31, the cable 5, the connector 29 and the connection part 26. The down-control signal includes an asynchronous signal. For example, this asynchronous signal has a bit rate of 600 bps in the case where the coupled portable telephone set 3 is a mobile telephone set, and has a bit rate of 2400 bps in the case where the coupled portable telephone set 3 is a PHS telephone set. For the sake of convenience, it is assumed that the CPU 2 is set to receive the asynchronous signal of 600 bps in the initial state. The process shown in FIG. 13 is called when a reception interrupt is generated from the portable telephone set 3.

A step S31 decides whether or not a reception error is generated in a state where the

5

10

30

5                   FIG. 14 is a flow chart for explaining the  
operation of the CPU 22 of the DCE 2 in this fifth  
embodiment. As described above in conjunction with  
FIGS. 5 through 7, the ground pins and the open pins  
allocated to the connectors 31 and 29 are different  
10 for the case where the coupled portable telephone  
set 3 is a mobile telephone set and the case where  
the coupled portable telephone set 3 is a PHS  
telephone set. FIG. 15 is a diagram showing the  
ground pins and the open pins allocated to the  
15 connector 29, with respect to the mobile telephone  
set and the PHS telephone set. In FIG. 15, "G"  
denotes the ground, "O" denotes the open-circuit,  
and "-" indicates neither the ground nor the open-  
circuit. In this embodiment, the combination of the  
20 pin numbers of the ground pins of the connector 29  
detected by the CPU 22 is compared with the  
combinations shown FIG. 15, so as to determine  
whether the coupled portable telephone set 3 is a  
mobile telephone set or a PHS telephone set.

25           A step S41 decides whether the coupled  
portable telephone set 3 is a mobile telephone set  
or a PHS telephone set, by comparing the combination  
of the pin numbers of the ground pins of the  
connector 29 detected by the CPU 22 with the  
30 combinations shown in FIG. 15. For example, if the  
combination of the pin numbers of the ground pins of  
the connector 29 detected by the CPU 22 is "1", "3",  
"9" and "14", it is judged that the coupled portable  
telephone set 3 is a mobile telephone set. If the  
35 step S41 decides that the coupled portable telephone  
set 3 is a mobile telephone set, a step S42 sets  
information which indicates the type of the portable

telephone set 3 as the mobile telephone set. On the other hand, if the step S41 decides that the coupled portable telephone set 3 is a PHS telephone set, a step S43 sets information which indicates the type of the portable telephone set 3 as the PHS telephone set. After the step S42 or S43, a step S44 issues a telephone set type primitive, so as to notify the identified type of the portable telephone set 3 to the personal computer 1 via the I/O control part 25, the connector 21 and the cable 4, and the process ends.

Next, a description will be given of a sixth embodiment of the telephone set identifying method according to the present invention. This sixth embodiment of the telephone set identifying method uses a sixth embodiment of the telephone set type identifying apparatus according to the present invention. The construction of the system applied with this sixth embodiment of the telephone set identifying method is the same as that applied with the first embodiment of the telephone set identifying method described above in conjunction with FIG. 1, and the basic construction of each part of the system in this sixth embodiment is the same as the basic construction of the corresponding part used in the first embodiment.

FIG. 17 is a flow chart for explaining the operation of the CPU 22 of the DCE 2 in this sixth embodiment. As shown in FIGS. 16A and 16B, the frequency of a frame signal used in the portable telephone set 3 is different between the mobile telephone set and the PHS telephone set. FIG. 16A shows a TCH frame signal having a frequency of 50 Hz which is used as the frame signal in the mobile telephone set, and FIG. 16B shows a down-frame clock having a frequency of 200 Hz which is used as the frame signal in the PHS telephone set. In this

embodiment, the CPU 22 detects the frequency of the frame signal received from the portable telephone set 3, so as to judge whether the coupled portable telephone set 3 is a mobile telephone set or a PHS telephone set.

The frame signal which is output from the portable telephone set 3 which is coupled to the DCE 2, is received at the port "b" of the CPU 22 via the connector 31, the cable 5, the connector 29 and the connection part 26. A step S51 detects the frequency of the frame signal received at the port "b". A step S52 decides whether the detected frequency of the frame signal is 50 Hz corresponding to the mobile telephone set or 200 Hz corresponding to the PHS telephone set. If the frequency of the frame signal detected in the step S52 is 50 Hz, the received frame signal is a TCH frame signal from a mobile telephone set, and it is judged that the coupled portable telephone set 3 is the mobile telephone set. In this case, a step S53 sets information which indicates the type of the portable telephone set 3 as the mobile telephone set. On the other hand, if the frequency of the frame signal detected in the step S52 is 200 Hz corresponding to the PHS telephone set, the received frame signal is a down-frame clock from a PHS telephone set, and it is judged that the coupled portable telephone set 3 is the PHS telephone set. In this case, a step S54 sets information which indicates the type of the portable telephone set 3 as the PHS telephone set. After the step S53 or S54, a step S55 issues a telephone set type primitive, so as to notify the identified type of the portable telephone set 3 to the personal computer 1 via the I/O control part 25, the connector 21 and the cable 4, and the process ends.

In each of the embodiments described above,



the type of the portable telephone set 3 identified by the DCE 2 can be notified using a serial line coupled to the personal computer 1, by use of the cable 4. FIG. 18 is a diagram showing the

5 notification of the type of the portable telephone set 3 identified by the DCE 2 to the personal computer 1. In FIG. 18, when the portable telephone set 3 is coupled to the DCE 2 and the DCE 2 identifies the type of the portable telephone set 3,

10 a character indication "PHONE: 1", for example, is output to the serial line so as to notify the identified type of the portable telephone set 3 to the personal computer 1. Accordingly, at the personal computer 1, it is possible to know the type

15 of the coupled portable telephone set 3 from the notified character indication. For example, the personal computer 1 can carry out processes, such as making a communication process between a communication application in a higher level or layer,

20 by switching a communication controlling software which controls the communication depending on the type of the portable telephone set 3.

In other words, when the personal computer 1 is notified of the type of the portable telephone set 3 identified by the DCE 2 in FIG. 19, an

25 operating system OP1 of the personal computer 1 can know the type of the portable telephone set 3 which is coupled to the personal computer 1 via the DCE 2. In a case where the type of the portable telephone

30 set 3 is the mobile telephone set, the communication controlling software which controls the communication depending on the type of the portable telephone set 3 is switched to a communication controlling application apl. On the other hand, in

35 a case where the type of the portable telephone set 3 is the PHS telephone set, the communication controlling software which controls the

5

10

35

FIG. 20 is a system block diagram showing the general construction of the main body part 101 of the personal computer 1 which uses this embodiment of the storage medium. The personal computer 101 includes a CPU 11, a hard disk drive (HDD) 12, a ROM 14, a disk unit 15 and an ASIC communication LSI 16 which are coupled via a bus 19 as shown in FIG. 20, and a hard disk 13 which is driven by the HDD 12. A connector 17 which corresponds to the connector 29 is connected to the communication LSI 16. As shown in FIG. 21, this connector 17 is coupled to the connector 31 of the portable telephone set 3 via the cable 5. The communication LSI 16 includes a communication function (asynchronous serial control and synchronous serial control) of the personal computer 101, and a function of controlling the I/O ports. The communication LSI 16 forms a PCI or an ISA bus interface, for example, with respect to the bus 19 of the personal computer 1.

25           For example, this embodiment of the  
storage medium is formed by the disk 110 shown in  
FIG. 2, and stores a program for realizing one of  
the first through sixth embodiments of the telephone  
set identifying method described above or, an  
30   arbitrary combination of the first through sixth  
embodiments of the telephone set identifying method  
described above. The program which is read from the  
disk 110 by the disk unit 15 is installed, for  
example, in the hard disk 13 via the HDD 12, under  
35   the control of the CPU 11. Hence, the CPU 11  
carries out one of or an arbitrary combination of  
the processes described above in conjunction with

5 identified within the personal computer 1, and thus,  
in this embodiment, the step of notifying the  
identified type of the portable telephone set 3 to  
the personal computer 1 in each of the first through  
sixth embodiments notifies the identified type to an  
10 operating system or an application having a higher  
level or layer.

FIG. 22 is a diagram showing the general structure of a software architecture of the personal computer 1. Various applications and drivers shown in FIG. 22 are provided under the operating system OP shown in FIG. 19. A personal computer communication application 603, an asynchronous PPP driver 602 and a TCP/IP communication application 601 such as a browser, are respectively provided as application in the higher level or layer, with respect to a communication port driver 604, and carry out various kinds of communication control. The communication port driver 604 is provided as an application in a higher level or layer, with respect to a pseudo serial driver group 605, and carries out various kinds of port driver control. The pseudo serial driver group 605 includes a communication controlling application (mobile telephone driver) ap1 which controls the communication for a mobile telephone set when the coupled portable telephone set 3 is the mobile telephone set, a communication controlling application (PHS telephone driver) ap2 which controls the communication for a PHS telephone set when the coupled portable telephone set 3 is the PHS telephone set, and an identifying application (identification driver) ap3 which identifies the type of the coupled portable telephone set 3. The

program stored in this embodiment of the storage medium includes at least the identifying application (identification driver) ap3. The pseudo serial driver group 605 can communicate with the portable telephone set 3 via the communication LSI 16 shown in FIG. 21.

Therefore, this embodiment of the storage medium can provide a driver such as the identifying application (identification driver) ap3, with respect to an application in the higher level or layer such as the communication port driver 604.

It is conceivable to construct a DCE apparatus which is provided with both a DCE designed exclusively for the mobile telephone set and a DCE designed exclusively for the PHS telephone set. But in this case, the hardware construction becomes complex, and it becomes difficult to reduce both the size and cost of the DCE apparatus. On the other hand, according to the present invention, the hardware used is the same regardless of the type of the portable telephone set, and the required process with respect to the mobile telephone set or the PHS telephone set is carried out by automatically identifying the type of the portable telephone set and switching the software. For this reason, the present invention does not require a complex hardware, and it is possible to easily reduce both the size and the cost of the telephone set type identifying apparatus.

In addition, the shape of the connector used in the conventional portable telephone set is different depending on the type of the portable telephone set, in order to prevent the user from making an erroneous connection. Hence, although the number of pins used are the same for the connectors, connectors having various different shapes had to be manufactured and used for the corresponding types of

portable telephone sets. However, if it is possible to use connectors having the same shape regardless of the types of portable telephone sets, it would substantially simplify matters and also considerably  
5 reduce the cost of the connectors. In the present invention, it is possible to automatically identify and recognize within the DCE or within the personal computer, the type of the portable telephone set which is coupled to the DCE, and thus, the user does  
10 not need to be aware of the type of the portable telephone set which is to be coupled to the DCE. Therefore, no inconveniences are introduced in the present invention even if connectors having the same shape are used regardless of the type of the  
15 portable telephone sets.

Further, the present invention is not limited to these embodiments, but various variations and modifications may be made without departing from the scope of the present invention.

20

25

30

35